



# 离子消毒一体机

## INTEGRATED ION DISINFECTION MACHINE

### ACSmatt



- Double fan design to prevent PCB overheating.
- Maximum 12V output.
- Power: 30W
- Wifi connection control device.
- Four touch buttons, simple interface.
- The screen displays the working status in real time.
- DC low voltage output, safety guarantee.
- Pipe connection, easy to install.
- Built-in overload and overcurrent protection function.
- Fine and compact appearance, occupy small space.
- Built-in circuit board, working time is adjustable.



- 双风扇设计，防止电路过热
- 最大12V输出
- 功率：30W
- Wifi 连接控制设备
- 触摸式四按键，界面简洁
- 屏幕实时显示工作状态
- 直流低电压输出，安全保障
- 管道连接，安装方便
- 内置过载过流保护功能
- 外观精细小巧，占地小
- 内置电路板，工作时间可调

### 工业产品艺术设计

### Industrial product art design

Specification :	技术参数
型号 Model	ACSmart 300 ACSmart 600
尺寸 Dimensions	391X186X273mm
电源/频率 Power/Frequency	220V/50Hz
工作压力 Working Pressure	2.5Kg/cm <sup>2</sup>
最大流量 Maximum Water Flow	28m <sup>3</sup> /h
最大环境湿度 Max Environmental Humidity	95%
温度 Temperature	5~40°C
连接管道 Connection Pipe	De63

### Flow Chart 流程图

